

PREMIUM PACKAGE

VC999[®]



CLC1200 **Closed Loop Chiller**

Specifications:

BTU Per Hour	4080
Watts	1100-1300
In/Outlet Piping	1/2" NPT
Pump Specs	0.13 - 0.18 MPa (at 7L/min)
Tank Capacity	5 L
Voltage.	100-115V @ 50/60Hz 1 ph 200-230V @ 50/60Hz 1 ph
Dimensions (WxDxH)	377 x 500 x 615 mm 14.8 x 19.7 x 24.2 in
Shipping Weight	131 lbs, 59 k
Circulating Fluids.	Distilled Water, Ethylene Glycol (max 15% concentration)

**Stand-Alone Closed Loop Chiller with integrated pump and tank systems.
Ideal for thermoformer & Tray Sealer Packaging Lines.**

- Rated at ambient temperatures from 5° C to 40° C
- Hermetically sealed compressor
- Continuous duty, non-ferrous pump, 7 LPM (other pumps available)
- Non-ferrous piping system
- Submersed copper coil evaporator
- Stainless steel tank with fully welded stainless steel couplers (1.2 gallon capacity)
- Environmentally acceptable R134a refrigerant
- Wetted Materials - Stainless steel, Copper brazing, Bronze, Synthetic rubber
- Mounted on casters (feet option available)

VC999[®]

Call 800-728-2999 • Fax 816-472-1999 • Sales@VC999.com

A DIVISION OF
INAUEN GROUP